



2016 NAU ASCE CONCRETE CANOE

POLARIS

NORTHERN ARIZONA UNIVERSITY

CHELSIE KEKAULA

COLTON MCCONNELL

BRENT LIPAR

EVAN KAICHI

EMILY MELKESIAN

Project Description

- Design and construct a concrete canoe
 - Maximum length/width: 22 feet/3 feet
 - Minimum reinforcement percent open area: 40%
 - No stain or paint
- Participate in ASCE Pacific Southwest Conference (PSWC)
 - Judged on technical paper, oral presentation, final product, paddling races
- Galaxy theme



Figure 1: 2016 Concrete Canoe



POLARIS

Hull Design

Hull Design

- Maximum Length: 21 ft
- Maximum Width: 27 in (2 ft-3 in)
- Maximum Depth: 14 in (1 ft-2 in)
- Uniform Thickness: 0.5 in




Figure 2: Prolines Software Model




Figure 3: Longitudinal Cross Section



Hull Analysis

Improvements:

- Linear relationship to cubic function

Calculated Waterlines:

- Fully Submersed: 0.2 in
- 4-Person: 6.9 in
- 2-Men: 8.5 in
- 2-Women: 9 in




Figure 4: Buoyant Force vs. Waterline Comparison

Structural Analysis

Structural Analysis

- Hull Capacity vs Demand:
 - 1"x1"x.5" Panels: 1715.9 psi (425.24 psi)
 - WT-Shape Ribs: 5290.6 psi (425.24 psi)
 - Transverse Cross-Section:
 - Tension Face: 917.5 psi (145.7 psi)
 - Compression Face: 1319.5 psi (151.7 psi)




Figure 5: Longitudinal Moment Comparison




Figure 6: Transverse Moment Comparison



Concrete Mix Design

Concrete Constituents (% volume)

- EkkoMaxx Fly Ash: 21.2%
- Poraver (0.5-1mm): 36.0%
- 3M Glass Bubbles (K20 & S32): 23.7%
- BASF Black Liquid Pigment: 2.9%
- MB AE 90 Air Entrainer: 0.1%
- Water: 10.5%
- Additives: 5.6%
- BASF Master Fibers

Table 1: Structural Mix Properties

| | |
|-----------------------------|--------------------|
| Dry Unit Weight | 59 pcf (<62.4 pcf) |
| 28-day Compressive Strength | 1950 psi |
| 28-day Tensile Strength | 190 psi |
| 28-day Flexural Strength | 1230 psi |



Figure 7: Compression Test



Figure 8: Tensile Test








Figure 9: Flexural Test



Reinforcement

- Selected primary reinforcement from five different materials
 - Strength and elongation
 - SpiderLath Fiberglass Mesh
 - Tensile Strength: 756 lb.
 - Elongation: 0.25 in
 - Percent Open Area: 62.6%

Table 2: Reinforcement Alternatives

| Material | SpiderLath Fiberglass Mesh [6] | Dryvit Reinforcing Mesh [7] | TriAx Geogrid [8] | Parex Glass Fiber Reinforcing Mesh [9] | Glasgrid Pavement Reinforcing System [10] |
|-----------------|---|---|---|---|---|
| |  |  |  |  |  |
| Strength (lb) | 756 | 102 | 72 | 135 | 181 |
| Elongation (in) | 0.25 | .07 | 0.62 | .08 | .04 |



Reinforcement Overlap

- Created composite samples of reinforcement and concrete
- Represented placement of reinforcement in canoe
- Tested overlap lengths of 2 in., 4 in., and 6 in.
- All overlap lengths worked
 - Chose 4 in. to be conservative




Figure 10: Overlap Samples




Figure 11: Overlap Test



Figure 12: Reinforcement Placement



Post-Tensioning

- System composed of six 1/16" galvanized steel cables placed symmetrically about the centroid
- Cables tensioned to 95 lbs., resulting in 57 lbs. of tension after losses
 - Total axial compression: 342 lbs.
 - Aids in reducing large cracks




Figure 13: Post Tensioning System



Figure 14: Anchorage System



Figure 15: Post Tensioning Canoe



Canoe Pour and Curing



Figure 16: Spray 1/8" Concrete onto Mold



Figure 17: Apply Reinforcement over Ribs & Center



Figure 18: Apply Post-Tensioning



Figure 19: Apply Reinforcement




Figure 20: Trowel Final Layer of Concrete



Figure 21: Construct Curing Structure



Figure 22: Moisture Cure for 21-days



Finishing




Figure 23: Dry Sand Canoe



Figure 24: Wet Sand Canoe



Figure 25: Carve and Etch Concrete




Figure 26: Seal Canoe



Final Product



Figure 27: Completed Ribs



Figure 28: Stern Design



Figure 29: 3D Element



Figure 30: Bow Design



POLARIS

Conference Results

- 6th place overall finish
- 3rd place for design paper
- 4th place for final product
- 13th place for racing
- 15th place for oral presentation



Figure 31: Canoe at Conference



Figure 32: Team Photo



Figure 33: Conference Display



Figure 34: Canoe Cutaway Section

Schedule

Table 3: Scheduled versus Actual Completion Date

| Task | Scheduled Completion Date | Actual Completion Date |
|--|---------------------------|------------------------|
| 1.0 Project Management | | |
| 1.1 Safety Training | 9/11/2015 | 9/11/2015 |
| 1.2 ASCE Competiton Rule Review | 10/2/2015 | 10/2/2015 |
| 1.3 Budgeting, Fundraising and Scheduling | Ongoing | Ongoing |
| 2.0 Testing and Analysis | | |
| 2.1 Reinforcement Selection | 12/11/2015 | 12/11/2015 |
| 2.2 Concrete Mix Design Selection | 1/15/2016 | 2/1/2016 |
| 2.3 Concrete-Reinforcement Composite Testing | 1/31/2016 | 2/27/2016 |
| 2.4 Structural Verification | 1/29/2016 | 2/6/2016 |

| Task | Scheduled Completion Date | Actual Completion Date |
|--|---------------------------|------------------------|
| 3.0 Construction | | |
| 3.1 Renovate canoe mold, coffin | 1/18/2016 | 1/18/2016 |
| 3.2 Pour Day Prep | 2/10/2016 | 2/11/2016 |
| 3.3 Pour Day | 2/12/2016 | 2/12/2016 |
| 3.4 Canoe Sanding/ Finishing | 3/19/2016 | 3/28/2016 |
| 4.0 ASCE Pacific Southwest Conference | | |
| 4.1 Internal Design Report Due | 2/15/2016 | 2/23/2016 |
| 4.2 Final Design Report Due | 3/2/2016 | 3/2/2016 |
| 5.0 CENE 486: Capstone Deliverables | | |
| 5.1 50% Design Report | 3/10/2016 | 3/10/2016 |
| 5.2 Final Deliverables | 5/12/2016 | 5/12/2016 |

Key

| |
|-------------------|
| Completed On-Time |
| Completed Late |

Cost

Table 4: Actual Cost of Engineering Services

| 1.0 Personnel | | | | |
|----------------|--------------|----------|------|----------|
| Classification | Billing Rate | Quantity | Unit | Cost |
| SENG | \$95 /hr | 295 | hr | \$28,025 |
| ENG | \$64 /hr | 260 | hr | \$16,640 |
| LAB | \$35 /hr | 225 | hr | \$7,875 |
| INT | \$13 /hr | 80 | hr | \$1,040 |
| AA | \$33 /hr | 235 | hr | \$7,755 |
| Total Cost | | | | \$61,335 |

| 2.0 Travel | | | | |
|-------------------------|---------------|----------|--------|---------|
| Item | Billing Rate | Quantity | Unit | Cost |
| Conference Registration | \$150 /person | 7 | people | \$1,050 |
| Lodging/ Food | \$250 /person | 7 | people | \$1,750 |
| Mileage | \$0.56 /mile | 940 | miles | \$526 |
| Total Cost | | | | \$3,326 |

| 3.0 Expenditures | | | |
|------------------|---------|----------|---------|
| Item | Price | Quantity | Cost |
| Materials | \$4,850 | Lump Sum | \$4,850 |
| Equipment | \$1,500 | Lump Sum | \$1,500 |
| Total Cost | | | \$6,350 |

| | |
|---------------------|----------|
| Total Project Cost | \$71,011 |
| Total Proposed Cost | \$76,943 |

Saved almost \$6,000

- ~ \$4,000 in Personnel
- ~ \$1,000 in Travel
- ~ \$1,000 in Expenditures



Impacts

Institutional Impacts


- Provides civil engineering students hands-on practical experience and improves leadership skills
- Knowledge and lessons learned for future NAU teams
- NAU Civil Engineering Department

Broader Impacts

- Use of CeraTech's EkkoMaxx cement – 100% sustainable material
- Increases awareness among students, educators, and professionals of concrete technology and innovation

Acknowledgements

Mark Lamer
Thomas Nelson
Gary Slim
Robin Tuchscher
Chris Hazel
Gina Boschetto
Dillion Corrington
Stephanie Crocker
Hudson & Ann Kekaula
Kaipo Kekaula
Jimmie McConnell
Wendy McConnell



Melkesian Family
Kaichi Family
Tommy Perkins
Jeremy DeGeyter
Cynthia Alvarez
Henry and Glenna Wong
Hank and Merle Miyamoto
Zach Crimmins
Paige Reilly
Ian Connair
Brando Gutierrez



POLARIS

References

- [1] ASTM (2004). “Compressive Strength of Cylindrical Concrete Specimens”, C 39/C 39M-01, West Conshohocken, PA.
- [2] ASTM (2011). “Standard Performance Specification for Hydraulic Cement.” C1157/C1157M-11, West Conshohocken, PA.
- [3] ASTM (2010). “Standard Specification for Fiber-Reinforced Concrete.” C1116/C1116M-10a, West Conshohocken, PA.
- [4] ASTM (2016). “Standard Test Method for Flexural Strength of Concrete (Using Simple Beam with Third-Point Loading)”, C78 / C78M-15b, West Conshohocken, PA.
- [5] CeraTech (2012). CeraTech EkkoMAXX™: General Product Information and Specifications. URL: <http://www.ceratechinc.com/Content/PDFs/ekkomaxx%20Green%20Concrete%20MSDS.pdf>> (Sep. 9, 2015). Web.
- [6] SpiderLath URL:<http://compositesandarchitecture.com/?p=3212>
- [7] Photo taken by 2014-2015 Concrete Canoe Team
- [8] Photo taken by 2014-2015 Concrete Canoe Team
- [9] Photo taken by 2014-2015 Concrete Canoe Team
- [10] Photo taken by 2014-2015 Concrete Canoe Team

THANK YOU

Presenting:
POLARIS

